

Technical Information BIO FOREST OIL

I. Intended use

The oil is designed to lubricate, cool and dampen vibrations in the cutting systems of mechanical saws

2. Advantages

- The oil is produced on a vegetable oil basis and is environmentally friendly.
- Absorbs vibrations and noise well.
- Ensures effective cooling.
- No varnishing.
- Efficient product, low oil consumption.
- Has excellent lubricating and maintenance properties for the cutting system.

- Is biodegradable, and has been tested **according to OECD 301 Method B, C, D, F** in accordance with the methodology of Commission Regulation (EC) No. 440/2008 of 30 May 2004 laying down test methods pursuant to Regulation (EC) No. 1907/2006.6.

- Oil also tested according to CECL-33-A-94 methodology, result biodegradability of 96%.

- In addition, the product has been tested by the Faculty of Forestry and Wood Technology of the Poznań University of Life Sciences, the results confirm the exquisite performance parameters of the oil, which is why the University recommends it.

- A high-quality product available at a very competitive price.

3. Variants available

The product is available in packs: 1 litre, 5 litres, 200 litres, 1000 litres.

4. <u>Storage and transport</u>

5. Store the product in tightly closed containers at a temperature of from -20 °C to 30 °C.

Protect from direct sunlight, away from sources of heat and open flame. It can be transported by any means of transport. Not subject to ADR regulations.

6. Safety precautions

The oil is not toxic or hazardous to humans. Apply the OSH and firefighting regulations, rules and requirements applicable to working with this product as described in the manufacturer's Product Data Sheet. It has PZH approval no. HK/ B/1337 /01/2015.

7. Warranty

For use within 12 months from the date of manufacture.